



## MP 2 & MP 3 LITHIUM GREASE

### PERFORMANCE PROFILE:

- ISO L- XBCDA2 Classification
- DIN 51825 K2K-20
- GA classification ASTM D 4950

### APPLICATION:

These are Multipurpose Greases based on Lithium soap designed to meet the lubrication requirements of all automotive and selected industrial grease applications. This includes all bearings and wheel hubs of cars, trucks, trailers and earthmoving equipment, universal joints and water pump bearings. These greases are recommended for normal loads and for operating temperatures not exceeding 135 deg C. These greases are fortified with antioxidant, antitrust and anticorrosion additives. They resist normal water washing and give excellent performance as a wheel bearing and general bearing grease.

### KEY FEATURES:

- Good wheel bearing performance
- Resistance to normal water-washing
- Protection against rusting
- Good pumpability
- Good resistance to shear under stress

### TECHNICAL DATA :

	TEST METHOD	MP2	MP3
Thickener Tye	-	Lithium	Lithium
NLGI Classification	ASTM D 217	2	3
Texture	-	Smooth	Smooth
Colour	-	Brown	Brown
Drop point , deg C	ASTM D 566	185	195
Worked penetration @25 degC/60strokes,0.1mm	ASTM D 217	265/295	220/250
Wheel bearing leakage after 6hrs@110 degC,gms	ASTM D 1263	< 2	< 2